



# SPARTAN™ Dry Cement Hose 3/16" SBR Tube Series SS187

Series SS187 is a gravity flow and low pressure discharge hose for dry cement and abrasive materials in bulk transfer applications. The static dissipating 3/16" SBR tube provides abrasion resistance and the SBR cover is resistant to abrasion, cuts, scuffs and weathering.

- Tube:** 3/16" Black SBR; static dissipating
- Reinforcement:** Multiple textile plies
- Cover:** Black SBR; wrapped finish
- Temp. Range:** -40°F to +180°F (-40°C to +83°C)
- Brand Method:** Black text on green stripe
- Brand Example:** PARKER SERIES SS187 MATERIAL HANDLING HOSE 50 PSI  
MADE IN USA
- Design Factor:** 4:1
- Industry Standards:** None applicable
- Applications:**
  - Abrasive dry materials, cement, lime, powders, silica
  - In-plant transfer/loading, bulk transport trucks
  - Construction, general industrial
- Vacuum:** Not recommended
- Packaging:** Coils

| Part Number | ID (in) | ID (mm) | Reinf Plies | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/ft) | Max Rec WP (psi) | Max Rec WP (bar) | Std Pack Qty (ft) | Stock Status ** |
|-------------|---------|---------|-------------|---------|---------|--------------------|-------------------|------------------|------------------|-------------------|-----------------|
| SS187-4000  | 4       | 101.6   | 2           | 4.595   | 116.7   | 1.85               | 0.84              | 50               | 3.4              | 100               | Y               |

\*\* **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

**⚠ WARNING!** Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. [Refer to the NAHAD Industrial Hose Assembly Guidelines.](#)